

**PRODUCT DATASHEET**

# CO-rekt™

**TRACE LEVEL IMPURITY ANALYZER  
FOR HYDROGEN**



## **Class I, Div. 2 For Hydrocarbon Feedstocks**

Just in time to meet the growing demand for high-quality hydrogen feedstock, our new CO-rekt™ analyzer brings the renowned benefits of Cavity Ring-Down Spectroscopy to your HyCO and SMR plants. This powerful, proven technology offers safe, fast and stable performance that allows you to efficiently manage your PSA beds to maximize yields and minimize contamination. The CO-rekt's dynamic range spans over four orders of magnitude, from parts-per-billion to parts-per-million. Other benefits include:

## Class I, Div. 2 For Hydrocarbon Feedstocks

- Drift-free performance: Avoid the downtime and labor cost tied to older technology's need for frequent calibration. The technology is so stable that it does not require calibration. No more need to store and to manage calibration cylinders or pay for complex sampling systems. And, remember, the less need for intervention, the less that can go wrong.
- Lack of consumables and spare parts: The CO-rekt is all solid state. Lose those pesky choppers and save on repair costs, as well as inventory management and storage space.
- Packaged for plant use: With Class I, Div. 2 certification, the CO-rekt combines a purged NEMA enclosure with a space-saving wall-mount configuration designed for narrow instrument sheds.
- Insensitive to vibration: No more plant trips triggered by the mere slam of a door to the instrument shed. Protects up-time bonuses and avoids fines.

---

Slam the door! Our analyzers are impervious to vibration and proven to stand up to long-term use in industrial applications. Designed in collaboration with one of the world's leading hydrogen manufacturers, the CO-rekt is guaranteed to increase uptime and decrease risk. Freedom from calibration and low cost of ownership allows users to operate with confidence and ease in the field.

---

## Specifications

### Performance

<b>Operating range:</b>	See table below
<b>Detection limit (LDL, 3<math>\sigma</math>/24h):</b>	See table below
<b>Precision (1<math>\sigma</math>, greater of):</b>	$\pm 0.75\%$ or 1/3 of LDL
<b>Accuracy (greater of):</b>	$\pm 4\%$ or LDL
<b>Speed of response:</b>	< 3 minutes to 90%
<b>Environmental conditions:</b>	10°C to 40°C 30% to 80% RH (non-condensing)
<b>Storage temperature:</b>	-10°C to 50°C

---

### Gas Handling System and Conditions

<b>Wetted materials:</b>	316L stainless steel (corrosive gas version optional) 10 Ra surface finish
<b>Gas connections:</b>	1/4" compression fittings inlet, outlet and purge
<b>Leak tested to:</b>	1 x 10 <sup>-9</sup> mbar l / sec
<b>Inlet pressure:</b>	10 – 125 psig (1.7 – 9.6 bara)
<b>Flow rate:</b>	Up to 1.8 slpm (gas dependent)
<b>Sample gases:</b>	Nitrogen and Hydrogen (inquire for custom matrices)
<b>Gas temperature:</b>	Up to 60°C

---

## Dimensions & Weight

**Standard sensor** (in NEMA 4X enclosure): H × W × D: 17.5 x 22 x 15.2 in (445 x 559 x 386 mm)

**Standard sensor weight:** 82 lbs (37.2 kg)

---

## Electrical and Interfaces

**Alarm indicators:** 2 user programmable, 1 system fault, Form C relays

**Power requirements:** 90 – 240 VAC, 50/60 Hz

**Power consumption:** 40 Watts max.

**Signal output:** Isolated 4–20 mA per sensor

**User interfaces:** 5.7" LCD touchscreen

**Certification:** Class I, Div. 2, Groups B, C & D

---

Performance in H <sub>2</sub>	Range	LDL (3σ)	Precision (1σ) @ zero
CO-rekt CO:	0 – 2000 ppm	150 ppb	50 ppb
CO-rekt CO <sub>2</sub> :	0 – 1500 ppm	500 ppb	170 ppb
CO-rekt H <sub>2</sub> O:	0 – 16 ppm	1.0 ppb	0.4 ppb
CO-rekt CH <sub>4</sub> :	0 – 100 ppm	7 ppb	2.5 ppb

Contact us for additional analytes, matrices and ranges.  
U.S. Patent # 7,277,177

## GAIN REAL-TIME INSIGHT INTO YOUR PROCESS

Process Insights manufactures and delivers premium sensors, monitors, detectors, analyzers, instrumentation, and software that are mission-critical to keep your operations, personnel, and the environment safe – every day across the globe.

Get the most reliable, precision analytical technologies available on the market today. We will work to match your needs and budget, and provide the optimal, and most stable process analysis solution for your application.

---

## CENTERS OF EXCELLENCE | PROVIDING PROVEN SOLUTIONS

Process Insights is committed to solving our customers' most complex analytical, process, and measurement challenges everyday.

### Process Insights – The Americas

4140 World Houston Parkway Suite 180, Houston, TX 77032, USA +1 713 947 9591

### Process Insights – EMEA

ATRICOM, Lyoner Strasse 15, 60528 Frankfurt, Germany +49 69 20436910

### Process Insights – APAC


Wujiang Economic and Technology, Development Zone, No. 258 Yi He Road, 215200 Suzhou, Jiangsu Province, China +86 400 086 0106

---

For a complete range of products, applications, systems, and service options, please contact us at: [info@process-insights.com](mailto:info@process-insights.com)

For a complete list of sales & manufacturing sites, please visit: <https://www.process-insights.com/about-us/locations/>

COSA Xentaur, Tiger Optics, Extrel, Alpha Omega Instruments, ATOM Instrument, MBW Calibration, MGA, Guided Wave, ANALECT and LAR TOC Leader are trademarks of Process Insights, Inc.



REVOLUTIONIZING MEASUREMENT

**EVERYWHERE**