

	Technology	Product	Liquids								Air & Gases	Steam	Multi-phase	Low Flows	High Flows	High Temp Rating	High Pressure Rating	Pipe Diameters (inches)
			Clean	Dirty	Corrosive	Viscous	Abrasive	Oil-Based Liquids	Ultra-Pure Water	Cryogenic								
Badger Meter® • Market leader in positive displacement meter technology • Rugged hand-held liquid dispensing options	Positive Displacement	Oval Gear	✓	ⓘ	▲	✓	ⓘ	✓	-	-	-	-	0.67 gpm	185 gpm	240° F	3000 psig	1/4...3	
		RCDL Nutating Disc	✓	-	▲	✓	-	✓	✓	-	-	-	0.5 gpm	170 gpm	250° F	150 psig	1/2...2	
		Pistol Grip Hand-held	✓	ⓘ	-	✓	ⓘ	✓	-	-	-	-	0.4 gpm	4 gpm	110° F	1000 psig	1/2	
		Universal Series	✓	-	-	✓	-	✓	-	-	-	-	0.4 gpm	4 gpm	150° F	1000 psig	1/2	
	PD Plus Turbine	RCDL Compound	✓	ⓘ	-	-	ⓘ	-	-	-	-	-	0.25 gpm	1500 gpm	120° F	150 psig	2...6	
	Turbine	RCDL Turbo	✓	ⓘ	-	-	ⓘ	-	-	-	-	-	4 gpm	19,800 gpm	120° F	150 psig	1-1/2...20	
		Industrial Turbo	✓	ⓘ	▲	▲	ⓘ	✓	ⓘ	-	-	-	8 gpm	2000 gpm	250° F	150 psig	2...6	
Vision		✓	-	ⓘ	-	-	✓	✓	-	-	-	0.03 gpm	9.25 gpm	212° F	363 psig	1/4...3/8		
ModMAG® • Complete line of mag meters for general purpose, sanitary and intrinsically-safe environments • 7500 Models feature built-in batch capability	Electromagnetic	M1000	✓	✓	▲	ⓘ	✓	-	-	-	-	0.01 gpm	6,279 gpm	140° F	ANSI 150 psig flange rating	1/4...8		
		M2000	✓	✓	▲	ⓘ	✓	-	-	-	-	0.06 gpm	1,100,000 gpm	311° F		1/4...54		
		M3000	✓	✓	▲	ⓘ	✓	-	-	-	-	0.02 gpm	53,778 gpm	248° F		1/4...24		
		M4000	✓	✓	▲	ⓘ	✓	-	-	-	-	0.02 gpm	13,444 gpm	122° F		1/4...12		
		M5000	✓	ⓘ	-	-	-	-	-	-	-	0.11 gpm	53,778 gpm	212° F		1/4...24		
Impeller • Proven flow metering solution • Full line of PVC and metal in-line designs support a wide range of facility applications from HVAC to submetering to irrigation • Some insertion models include hot-tap options	Impeller In-line	380 Btu Meter	✓	▲	-	-	-	-	-	-	-	1.7 gpm	157 gpm	260° F	400 psig	3/4...2		
		735	✓	▲	-	-	-	-	-	-	-	-	1.2 gpm	49 gpm	110° F	160 psig	1/2...1	
		4000	✓	▲	✓	-	-	ⓘ	✓	-	-	-	0.2 gpm	49 gpm	220° F	350 psig	1/2...1	
		228PV	✓	▲	ⓘ	-	-	-	-	-	-	-	2.8 gpm	1175 gpm	221° F	100 psig	1-1/2...4	
		228 Metal	✓	▲	ⓘ	-	-	-	-	-	-	-	0.3 gpm	459 gpm	221° F	300 psig	2...2-1/2	
	Impeller Insertion	250B	✓	▲	-	-	-	-	-	-	-	-	1.2 gpm	110 gpm	221° F	400 psig	1/2...1-1/2	
		SDI	✓	▲	ⓘ	-	-	-	-	-	-	-	0.3 fps	20 fps	300° F	1000 psig	1-1/2...36	
		220	✓	▲	ⓘ	-	-	ⓘ	-	-	-	-	0.3 fps	20 fps	221° F	400 psig	2...40+	
		220PVS	✓	▲	ⓘ	-	-	-	ⓘ	-	-	-	0.3 fps	20 fps	140° F	100 psig	2...40+	
		225	✓	▲	-	-	-	-	-	-	-	-	0.3 fps	20 fps	221° F	400 psig	2...40+	
Hedland® • Installation at any angle • Special scales available • Quick delivery	In-line Variable Area	High Pressure	✓	▲	✓	▲	-	▲	▲	-	-	0.02 gpm	400 gpm	500° F	6000 psig	1/4...3		
		EZ-View	✓	▲	▲	ⓘ	-	▲	▲	-	-	-	0.5 gpm	275 gpm	250° F	325 psig	1/2...3	
Dynasonics® • Ultrasonic Technology • No process shutdown on clamp-on • Large turndown ratio • Btu metering and data logging options	Transit Time	TFX-5000	✓	ⓘ	▲	ⓘ	ⓘ	ⓘ	✓	-	-	0.07 gpm	33,000 gpm	350° F	N/A	1/2+		
		TFX-500w	✓	-	-	-	-	-	✓	-	-	-	0.07 gpm	3,450 gpm	250° F	N/A	1/2...10	
	Doppler	DFX	ⓘ	✓	▲	▲	▲	ⓘ	-	-	▲	-	0.3 fps	30 fps	400° F	N/A	1/4+	
	Hybrid Portable	DXN	✓	✓	▲	▲	▲	ⓘ	✓	-	▲	-	0.001 fps	40 fps	350° F	N/A	1/4+	
	Inline Transit Time	U500w	✓	✓	-	-	-	-	-	-	-	-	0.1 gpm	1100 gpm	140° F	175 psig	5/8...4	
	Open Channel	iSonic 4000	✓	-	-	-	-	-	-	-	-	-	10 gpm	40,000 gpm	140° F	N/A	N/A	

✓ Designed for this Service

▲ Normally Applicable

ⓘ Consult Factory

- Not Applicable or Suitable

Flow Instrumentation Selection Chart

	Technology	Product	Liquids								Air & Gases	Steam	Multi-phase	Low Flows	High Flows	High Temp Rating	High Pressure Rating	Pipe Diameters (inches)
			Clean	Dirty	Corrosive	Viscous	Abrasive	Oil-Based Liquids	Ultra-Pure Water	Cryogenic								
Flo-tech • Single device measures flow, pressure, and temperature • High pressure capability • Rugged design	In-line Turbines	Activa, Ultima, Classic, Quad	✓	-	Ⓜ	Ⓜ	-	✓	-	-	-	-	0.4 gpm	350 gpm	300° F	6000 psig	1/4...2	
	Portable Hydraulic Testers	PFM, Flo-Check	✓	-	Ⓜ	Ⓜ	-	✓	-	-	-	-	1 gpm	200 gpm	300° F	6000 psig	3/4...1-1/2	
		MC4000	✓	-	Ⓜ	Ⓜ	-	✓	-	-	-	-	0.4 gpm	160 gpm	392° F	5800 psig	1/4...1-1/4	
Blancett® • Rugged, 316 SS w/tungsten carbide internal parts • ±1% accuracy liquid meters • Easy-to-install • Field-replaceable internal repair kits	In-line Turbines	1100	✓	▲	Ⓜ	Ⓜ	Ⓜ	▲	▲	-	-	-	0.6 gpm	5000 gpm	350° F	5000 psig	1/2...10	
		QuikSert	✓	▲	Ⓜ	Ⓜ	Ⓜ	▲	▲	-	-	-	0.6 gpm	5000 gpm	350° F	3705 psig	3/8...10	
		FloClean	✓	▲	Ⓜ	Ⓜ	Ⓜ	Ⓜ	▲	-	-	-	0.6 gpm	400 gpm	350° F	1000 psig	1...3	
		Gas QuikSert	-	-	-	-	-	-	-	-	-	✓	-	7 acfm	350 acfm	330° F	2220 psig	2
	Positive Displacement	B1750	✓	-	Ⓜ	✓	-	▲	Ⓜ	-	-	-	0.003 gpm	120 gpm	400° F	5000 psig	1/4...1-1/4	
Cox • High accuracy (up to ±0.10%) • Cost effective alternative to electronic metering options of similar accuracy • Suitable for high-vibration environments	High-Precision Turbine	Single Rotor	✓	-	▲	Ⓜ	Ⓜ	✓	✓	✓	-	-	0.007 gpm	310 gpm	500° F	7000 psig	1/4...2	
		Dual Rotor	✓	-	▲	Ⓜ	Ⓜ	✓	✓	✓	-	-	-	0.025 gpm	1500 gpm	300° F	3000 psig	1/4...4
Vortex • No moving parts • Corrosion resistant (RVL) • Stainless steel insertion (VN2000)	Vortex Shedding	RVL	✓	Ⓜ	▲	-	-	✓	-	-	-	-	0.6 gpm	300 gpm	203° F	150 psig	1/2...3	
		VN2000	✓	▲	Ⓜ	-	Ⓜ	Ⓜ	Ⓜ	-	-	✓	✓	1.32 fps	250 fps	400° F	1000 psig	2...36
Preso® • Ellipse Pitot tube has highest turndown ratio (17:1) and lowest permanent pressure loss among competitors • Very low Reynolds number (COIN meter)	DP Venturi	SSL, SSM, LPL	✓	▲	Ⓜ	Ⓜ	Ⓜ	✓	✓	▲	Ⓜ	✓	✓	✓	Application Dependent	1500° F	9000 psig	1/2...60
		CV	✓	▲	Ⓜ	Ⓜ	Ⓜ	✓	✓	-	Ⓜ	✓	-	-		250° F	300 psig	2...16
	DP Pitot Tubes	Ellipse	✓	Ⓜ	▲	Ⓜ	-	▲	✓	-	-	✓	✓	-		800° F	5500 psig	2...42
	DP Segmented Wedge	COIN	✓	✓	▲	✓	✓	✓	✓	▲	▲	✓	✓	✓		1500° F	9000 psig	1/2...48
	DP Cone	Cone	✓	Ⓜ	▲	Ⓜ	Ⓜ	✓	✓	▲	Ⓜ	✓	✓	✓		1000° F	9000 psig	1...16
Research Control® Valves • Low-flow control valves up to 2 inches • Wide variety of alloys • Engineered solutions	Control Valves	General Industrial	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	0.0000018 Cv	54 Cv	1800° F	60,000 psig	1/4...2	
		Sanitary	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	0.05 Cv	90 Cv	300° F	1500 psig	1/2...3
Coriolis • Unobstructed open flow design • High accuracy (up to ±0.10%) • Advanced fluid diagnostic tools	Mass Flow	RCT1000	✓	✓	Ⓜ	✓	Ⓜ	✓	-	Ⓜ	-	-	0.05 lb/min	5200 lb/min	392° F	3000 psig	1/16...3	
Flow Dynamics® • Primary Standard Calibration Service • Liquid calibration uncertainty: ±0.025% to ±0.05% of reading • Gas calibration uncertainty: ±0.20% to ±0.25% of reading • NVLAP (Lab Code 200668-0) accredited traceable to NIST (ISO/IEC 17025 - ANSI/NCL Z540) • Liquids: water, solvent (1.2 cSt), and oil blends (0.7 to 1300 cSt); consult factory above 1300 cSt • Gases: Air, Nitrogen, Helium, Argon, Methane, Propane, and others	Positive Displacement Calibrations	Liquid Calibration Service	✓	-	-	✓	-	✓	✓	-	-	-	0.0025 gpm	1500 gpm	140° F	120 psig	1/4...4	
	Bell Provers, Glass Tube & Sonic Nozzles	Air/Gas Calibration Service	✓	-	-	-	-	-	-	-	-	✓	-	0.00035 scfm	1000 scfm	N/A	500 psia	1/4...4

Note: NVLAP accreditation applies only to the Badger Meter Flow Dynamics calibration Lab, located in Racine, WI.

✓ Designed for this Service ▲ Normally Applicable Ⓜ Consult Factory - Not Applicable or Suitable